Eolis® mobile workstations

• Single piece case made from mechanically welded epoxy steel, closed on 5 sides with roof and bottom. Open face on 600 side.

Villard

- Workstation made from highdensity compact resin class M1, 10 mm thick with antibacterial treatment. Effectiveness tested to 99.9% on 7 bacteria according to standard JISZ 2801.
- ABS internal ladders with a capacity of 9, 2 x 9 or 3 x 9 levels (according to the model) making it possible to equip the block with drawers and perforated baskets ISO 600 x 400 as well as all the internal elements of the Eolis range (ISO tray with nominative pill dispensers and drawers).
- 4, 6 or 8 swivel wheels Ø 125 mm (according to the model) made of polyamide with threadguards of which 2, 3 or 4 with brakes, stainless steel ball bearings.



EOLIS® MOBILE WORKSTATIONS



MODEL CAPACITY DIM. L X D X H REF. Simple 9 levels 680 x 490 x 965 mm 1007.11 Double 1007.12 2 x 9 levels 1325 x 490 x 965 mm With drawers Triple 3 x 9 levels 1966 x 490 x 965 mm 1007.13 Double with central space 2 x 9 levels 2030 x 490 x 965 mm 1007.14 Simple, back-to-back 2 x 9 levels 1048 x 680 x 965 mm 1007.15 Simple 8 levels 685 x 595 x 935 mm 1007.61 With rolling shutter Double 2 x 8 levels 1335 x 565 x 935 mm 1007.62

Ð	OPTIONS	REF.
	Side rail for workstation	1700.22
	Simple bridge for workstation	1700.23

Options and accessories for Eolis[®] mobile workstations

	OPTIONS FOR EOLIS® MOBILE WORKSTATIONS				
		MODEL		WITH DRAWERS	WITH ROLLING SHUTTER
1700.13	Central locking	with key 		1700.01	1700.10
1700.13				1700.03	1700.12
		with code +	key	1700.04	1700.13
	Supplement for Corian® tray	Simple		1700.52	1700.55
		Double		1700.53	1700.56
		Triple		1700.54	1700.57
	Supplement for tray Depth 570 mm	Compact resin	Simple	1700.65	1700.73
			Double	1700.66	1700.74
			Triple	1700.67	1700.75
			Double with central space	1700.68	-
1700.65		Corian®	Simple	1700.69	1700.77
-			Double	1700.70	1700.78
			Triple	1700.71	1700.79
			Double with central space	1700.72	-
	Supplement for backboard Height 100 mm	Compact resin	Simple	170).84
			Double	1700).85
1700.84			Triple	170).86
1700.04			Double with central space	1700).87

Suspended workstations

• Workstation made from highdensity compact resin class M1, 13 mm thick with antibacterial treatment. Effectiveness tested to 99.9% on 7 bacteria according to standard JISZ 2801.

ß	OPTIONS	REF.
	Pair of brackets for suspended workstation	1008.20
•	ACCESSORIES	REF.
	Additional bracket (from 1400 mm)	1008.21

1008.04	1008.20
SUSPENDED WORKSTATIONS	
MODEL	WITHOUT WITH BACKBOARD BACKBOARD
L 800 mm	1008.01 1008.10
L 1000 mm	1008.02 1008.11
L 1200 mm	1008.03 1008.12
L 1400 mm (3 brackets needed)	1008.04 1008.13
L 1600 mm (3 brackets needed)	1008.05 1008.14
L 1800 mm (3 brackets needed)	1008.06 1008.15
L 2000 mm (3 brackets needed)	1008.07 1008.16