KERN FES33K-4

Measuring system



High-capacity precision balance with password-protected user administration, also with EC type approval [M]



Adjustment options:	External calibration
Eccentric loading at 1/3 [Max]:	300 mg
Linearity:	300 mg
Minimum weight (USP):	200 g
Readability [d]:	100 mg
Recommended adjusting weight:	20 kg (E2); 10 kg (E2)
Repeatability:	100 mg
Resolution:	330000
Stabilisation time under laboratory conditions:	3 s
Tare range:	33 kg
Warm up time:	2 h
Weighing capacity [Max]:	33 kg
Weighing units:	ct oz ozt tl (HK) tol g kg lb tl (Singap. Malays) dwt tl (Tw)
Weighing units: Display	` , ,
	` , ,
Display	(Singap. Malays) dwt tl (Tw)
Display Display digit height (large):	(Singap. Malays) dwt tl (Tw) 1,650 cm
Display Display digit height (large): Display digit height (small):	(Singap. Malays) dwt tl (Tw) 1,650 cm
Display Display digit height (large): Display digit height (small): Counting	(Singap. Malays) dwt tl (Tw) 1,650 cm 8,500 mm

Functions	
Capacity display:	yes
Counting function:	yes
Function to save totals:	yes
Percentage determination:	yes
PRE-TARE function:	yes
Standby function:	yes
Weighing with tolerance range:	yes
Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	35 °C
Minimum ambient temperature:	5°C
Power supply	
Charging time:	12 h
Input voltage:	100 V - 240 V AC 50 / 60 Hz
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	US UK EURO AUS
Operating time (Backlight off):	10 h
Rechargeable battery:	Rchrg. battery optional
	(factory)
Services (optional)	
DAkkS Certificate:	963-128
Category	
Brand:	KERN
Category:	Balances
Product Group:	Precision balance
Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	490 x 830 x 430 mm
Gross weight:	24 kg
Net weight:	18 kg
Shipping method:	Parcel service
Construction	
Cable length of display device:	1 m
Dimensions housing (WxDxH):	350 x 520 x 170 mm
Dimensions of display device (WxDxH):	290 x 180 x 80 mm
Dimensions of weighing plate	400 x 350 x 150 mm

(WxDxH):

KERN FES33K-4



High-capacity precision balance with password-protected user administration, also with EC type approval [M]

Level indicator: yes

Material weighing plate: stainless steel

Revolving screw feet: yes Wall mount: yes

Weighing surface (WxD): 350 x 400 mm

Piktogramme

STANDARD



OPTION



FACTORY

