KERN UID600K-1DM



High-resolution dual-range pallet scale with calibration approval [M] and a large number of data interfaces



Measuring system					
Adjustment options:	External calibration				
Eccentric loading at 1/3 [Max]:	500 g 1000 g				
Linearity:	300 g 600 g				
Load cell connection:	4-wire				
Number of weighing ranges:	2				
Readability [d]:	100 g 200 g				
Repeatability:	100 g 200 g				
Resolution:	3 3.000				
Stabilisation time under laboratory conditions:	4 s				
Tare range:	-600 kg				
Warm up time:	10 min 10 min				
Weighing capacity [Max]:	300 kg 600 kg				
Weighing system:	Strain gauge				
Weighing units:	g oz PCS kg lb tJ HJ				
Display					
Display digit height (large):	2,500 cm				
Display digit height (small):	2,500 cm				

Technical data about verification

Minimum load [Min]:	2 kg 4 kg		
Periodic Verification for Italy:	969-112		
Verification approval conforming to 2014/31/EU:	yes		
Verification by KERN possible:	yes		
Verification class:	III		
Verification value [e]:	100 g 200 g		

Functions				
Counting function:	yes			
Data hold function:	yes			
Percentage determination:	yes			
Time display:	yes			
Vibration-free weighing (Animal weighing program):	yes			
Weighing with tolerance range:	yes			
Environmental conditions				
Maximum humidity:	95 %			
Maximum operating temperature:	40 °C			
Minimum ambient temperature:	-10 °C			
Minimum humidity:	10 %			
Power supply				
Battery:	no battery			
Charging time:	3 h			
Input voltage:	100V-240V AC 50/60Hz 0,400 Amax			
Mains adapter:	Mains adapter external			
Mains adapter/adapter included:	UK US EURO			
Operating time (Backlight off):	43 h			
Operating time (Backlight on):	26 h			
Rechargeable battery:	Rchrg. battery optional - intern			
Services (optional)				
Adjustment at the location of installation	:961-250			
DAkkS Certificate:	963-130			
Verification:	965-230			
Category				
Brand:	KERN			
Category:	Balances			
Product Group:	Pallet scale			
Packaging & shipping				
Delivery:	48 h			
Dimensions packaging (WxDxH):	1270 x 900 x 260 mm			
Gross weight:	65 kg			
Net weight:	44 kg			
Shipping method:	Freight forwarder			
Construction				
Cable length:	5 m			
Cable length of display device:	5 m			
Dimensions of display device	268 x 115 x 80 mm			

KERN UID600K-1DM



High-resolution dual-range pallet scale with calibration approval [M] and a large number of data interfaces

Dimensions of weighing plate (WxDxH):	1195 x 840 x 110 mm		
Level indicator:	yes		
Revolving screw feet:	yes		
Wall mount:	yes		
Weighing surface (WxD):	1195 x 840 mm		

Piktogramme

STANDARD

		KCP						
CAL EXT	RS 232	PROTOCOL	PCS	SUM	TOL	FAST-MOVE	IP 65	IP 67
A H	DMS	2 DAYS						

OPTION



FACTORY

	•	*	?	금무	Μ	
ALIBI	USB	BT 4.0	WIE	LAN	+3 DAYS	