# KERN MPS 200K100PM



Stylish personal floor scale with BMI function – with approval for professional medical use in medical diagnostics, verification optional



Kategorie	
Brand	KERN
Product categoriy	Medical scale
Product group	Personal floor scale
Product family	MPS

### Measuring System

,
1
Single-range balance
Strain gauge
200 kg
0,1 kg
2.000
± 0,1 kg
0,1 kg
kg
kg
2 kg
Adjusting with external weight
200 kg (M1)
10 min
0,1 kg
60-100cm @ 0,1cm ± 0,5cm 100-205cm @ 0,1cm ± 1cm

Approval	
CE mark	✓
Pattern approval for conformity assessment	1
Accuracy classe	III

Verification scale interval [e]	0,1 kg
Conformity assessment possible ex works	1
Approval according to 93/42/EEC (med.)	✓
Display	
Display type	LCD
Display digit height	27 mm
Languages of the user interface	Symbol language
Construction	
Dimension display device (W×D×H)	215×110×45 mm
Dimension display device (w^D^I)	215411044511111
(W×D×H)	275×295×58 mm
Dimensions completely mounted (W×D×H)	275×445×1020 mm
Material display housing	Plastics
Material housing	steel, lacquered
Material weighing plate	steel, lacquered
Levelling feet adjustable	1
Stand height	1000 mm
Functions	
Number of keys for operation	20
	3 min
Auto-off interval(s) in batterv	off
Auto-off interval(s) in battery mode/rechargeable battery mode	4 min
	4 min 5 min
mode/rechargeable battery mode	4 min 5 min 2 min
mode/rechargeable battery mode PreTare function	4 min 5 min 2 min
mode/rechargeable battery mode PreTare function Tare function	4 min 5 min 2 min ✓ manual (multi)
mode/rechargeable battery mode PreTare function Tare function Hold function	4 min 5 min 2 min
mode/rechargeable battery mode PreTare function Tare function	4 min 5 min 2 min ✓ manual (multi)
mode/rechargeable battery mode PreTare function Tare function Hold function Function for averaging under	4 min 5 min 2 min ✓ manual (multi)
mode/rechargeable battery mode PreTare function Tare function Hold function Function for averaging under unstable weighing conditions	4 min 5 min 2 min ✓ manual (multi) ✓
mode/rechargeable battery mode PreTare function Tare function Hold function Function for averaging under unstable weighing conditions Function for BMI calculation	4 min 5 min 2 min ✓ manual (multi) ✓ ✓
mode/rechargeable battery mode PreTare function Tare function Hold function Function for averaging under unstable weighing conditions Function for BMI calculation Interfaces Power Supply Input voltage power supply /	4 min 5 min 2 min ✓ manual (multi) ✓ ✓ KS-232 standard 100 V - 240 V, 50 / 60
mode/rechargeable battery mode PreTare function Tare function Hold function Function for averaging under unstable weighing conditions Function for BMI calculation Interfaces Power Supply Input voltage power supply / power [Max]	4 min 5 min 2 min ✓ manual (multi) ✓ ✓ ✓ KS-232 standard 100 V - 240 V, 50 / 60 Hz
mode/rechargeable battery mode PreTare function Tare function Hold function Function for averaging under unstable weighing conditions Function for BMI calculation Interfaces Power Supply Input voltage power supply / power [Max] Input voltage device / power [Max]	4 min 5 min 2 min ✓ manual (multi) ✓ ✓ KS-232 standard 100 V - 240 V, 50 / 60 Hz 12 V, 500 mA
mode/rechargeable battery mode PreTare function Tare function Hold function Function for averaging under unstable weighing conditions Function for BMI calculation Interfaces Power Supply Input voltage power supply / power [Max]	4 min 5 min 2 min ✓ manual (multi) ✓ ✓ KS-232 standard 100 V - 240 V, 50 / 60 Hz 12 V, 500 mA Power adapter
mode/rechargeable battery mode PreTare function Tare function Hold function Function for averaging under unstable weighing conditions Function for BMI calculation Interfaces Power Supply Input voltage power supply / power [Max] Input voltage device / power [Max]	4 min 5 min 2 min ✓ manual (multi) ✓ ✓ ✓ S-232 standard 100 V - 240 V, 50 / 60 Hz 12 V, 500 mA Power adapter Power supply & battery function (battery not
mode/rechargeable battery mode PreTare function Tare function Hold function Function for averaging under unstable weighing conditions Function for BMI calculation Interfaces Power Supply Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type	4 min 5 min 2 min ✓ manual (multi) ✓ ✓ ✓ S-232 standard 100 V - 240 V, 50 / 60 Hz 12 V, 500 mA Power adapter Power supply & battery function (battery not included)
mode/rechargeable battery mode PreTare function Tare function Hold function Function for averaging under unstable weighing conditions Function for BMI calculation Interfaces Power Supply Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type	4 min 5 min 2 min ✓ manual (multi) ✓ ✓ ✓ S-232 standard 100 V - 240 V, 50 / 60 Hz 12 V, 500 mA Power adapter Power supply & battery function (battery not
mode/rechargeable battery mode PreTare function Tare function Hold function Function for averaging under unstable weighing conditions Function for BMI calculation Interfaces Power Supply Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply Plug-in power supply	4 min 5 min 2 min ✓ manual (multi) ✓ ✓ ✓ KS-232 standard 100 V - 240 V, 50 / 60 Hz 12 V, 500 mA Power adapter Power supply & battery function (battery not included) EURO

KERN & SOHN GmbH · Ziegelei 1 · 72336 Balingen · Germany · Tel. +49-(0)7433 - 99 33-0 · www.kern-sohn.com

# KERN MPS 200K100PM



Stylish personal floor scale with BMI function – with approval for professional medical use in medical diagnostics, verification optional

Plug-in power supply / adapter for countries - optional	EURO UK US CH
Rechargeable battery optional	Rchrg. battery optional - intern
Rechargeable battery charging time	14 h
Rechargeable battery operating time - backlight off	35 h
Battery	6×1.5 V AA
Battery operating time	50 h

# Environmental conditions

Humity of environment [Max]	80 %
Ambient temperature [Min]	5 °C
Ambient temperature [Max]	35 °C
Storage temperature [Min]	-20 °C
Storage temperature [Max]	60 °C

### Packing & Shipping

Readability force [d] (N)	1 d
Shipping method	Parcel service
Dimensions packaging (W×D×H)	1180×400×330 mm
Net weight approx.	7 kg
Gross weight approx.	11 kg
Shipping weight	31,2 kg

#### Services (optional)

Article number for adjustment at the location of installation	961-249
Article number for conformity assessment	965-129
Article number for DAkkS calibration	963-129
Article number for certificate of conformity (verification)	969-517

## Pictograms

#### STANDARD



#### OPTION



FACTORY

