# KERN GAB6K0.05N

Checkweighing and portioning scale, also with EC type approval [M]





Measuring system	
Adjustment options:	External calibration
Eccentric loading at 1/3 [Max]:	250 mg
Linearity:	150 mg
Readability [d]:	50 mg
Recommended adjusting weight:	6 kg (F2)
Repeatability:	50 mg
Resolution:	120000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-6 kg
Warm up time:	2 h
Weighing capacity [Max]:	6 kg
Weighing system:	Strain gauge
Weighing units:	g oz kg t lb

-1 -7 - 3 3 - ( - 3 - 7	,	
Counting		
Counting resolution:	120000	
Mininum piece weight at piece counting (Laboratory:	50 mg	
Mininum piece weight at piece counting (Normal):	500 mg	

2,400 cm

Display

Display digit height (large):

Functions		
Counting function:	yes	
Function to save totals:	yes	
Percentage determination:	yes	
Weighing with tolerance range:	yes	

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	0°C

Power supply	
Charging time:	12 h
Input voltage:	220 V - 240 V AC 50 Hz
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	EURO UK CH
Operating time (Backlight off):	90 h
Operating time (Backlight on):	40 h
Rechargeable battery:	Rchrg. battery optional - intern

Category	
Brand:	KERN
Category:	Balances
Product Group:	Bench scale

963-128

Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	445 x 375 x 205 mm
Gross weight:	4,418 kg
Net weight:	3 kg
Shipping method:	Parcel service


Construction	
Casing material:	Plastic
Dimensions housing (WxDxH):	315 x 350 x 100 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Overall dimensions mounted (WxDxH):	315 x 350 x 125 mm
Revolving screw feet:	yes
Weighing surface (WxD):	295 x 225 mm

## Piktogramme

Services (optional)

DAkkS Certificate:

### STANDARD



#### OPTION



#### **FACTORY**

