KERN ACS80-4



The bestseller in analytical balances, with high-quality single-cell weighing system, also with EC type approval [M]



Measuring system

Adjustment options:	External calibration
Eccentric loading at 1/3 [Max]:	0,500 mg
Linearity:	0,300 mg
Minimum weight (USP):	400 mg
Readability [d]:	0,100 mg
Recommended adjusting weight:	80 g (E2)
Repeatability:	0,200 mg
Resolution:	820000
Stabilisation time under laboratory conditions:	3 s
Warm up time:	4 h
Weighing capacity [Max]:	82 g
Weighing units:	g mg

Display

Display digit height (large):

Counting

Counting resolution:	82000
Mininum piece weight at piece counting (Laboratory:	1 mg
Mininum piece weight at piece	10 mg

Reference weight:	yes			
Functions				
Counting function:	yes			
Function to save totals:	yes			
Percentage determination:	yes			
Standby function:	yes			
Weighing with tolerance range:	yes			
Environmental conditions				
Maximum humidity:	85 %			
Maximum operating temperature:	30 °C			
Minimum ambient temperature:	10 °C			
Minimum humidity:	20 %			
Power supply				
Input voltage:	110 V - 230 V AC			
Mains adapter:	Mains adapter external			
Mains adapter/adapter included:	EURO CH UK US			
Services (optional)				
DAkkS Certificate:	963-101			
0				
Category				
Category Brand:	KERN			
	KERN Balances			
Brand:				
Brand: Category:	Balances			
Brand: Category: Product Group:	Balances			
Brand: Category: Product Group: Packaging & shipping	Balances Analytical balance			
Brand: Category: Product Group: Packaging & shipping Delivery:	Balances Analytical balance 24 h			
Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH):	Balances Analytical balance 24 h 390 x 565 x 520 mm			
Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight:	Balances Analytical balance 24 h 390 x 565 x 520 mm 8,900 kg			
Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight:	Balances Analytical balance 24 h 390 x 565 x 520 mm 8,900 kg 6,100 kg			
Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method:	Balances Analytical balance 24 h 390 x 565 x 520 mm 8,900 kg 6,100 kg			
Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction	Balances Analytical balance 24 h 390 x 565 x 520 mm 8,900 kg 6,100 kg Parcel service			
Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Casing material:	Balances Analytical balance 24 h 390 x 565 x 520 mm 8,900 kg 6,100 kg Parcel service Plastic			
Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Casing material: Dimensions draft shield (WxDxH):	Balances Analytical balance 24 h 390 x 565 x 520 mm 8,900 kg 6,100 kg Parcel service Plastic 201 x 220 x 256 mm			
Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Casing material: Dimensions draft shield (WxDxH): Dimensions housing (WxDxH):	Balances Analytical balance 24 h 390 x 565 x 520 mm 8,900 kg 6,100 kg Parcel service Plastic 201 x 220 x 256 mm 213 x 333 x 338 mm			
Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Casing material: Dimensions draft shield (WxDxH): Dimensions housing (WxDxH): Level indicator:	Balances Analytical balance 24 h 390 x 565 x 520 mm 8,900 kg 6,100 kg Parcel service Plastic 201 x 220 x 256 mm 213 x 333 x 338 mm yes			
Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Casing material: Dimensions draft shield (WxDxH): Dimensions housing (WxDxH): Level indicator: Material weighing plate:	Balances Analytical balance 24 h 390 x 565 x 520 mm 8,900 kg 6,100 kg Parcel service Plastic 201 x 220 x 256 mm 213 x 333 x 338 mm yes stainless steel			

1,400 cm

KERN ACS80-4



The bestseller in analytical balances, with high-quality single-cell weighing system, also with EC type approval [M]

Piktogramme

STANDARD

	Ĩ	•	GLP		≜ ^	%	-√+ ⊙	C
CAL INT	CAL EXT	USB	PRINTER	PCS	RECIPE	PERCENT	TOL	UNIT
B) E							
MULTI	SC TECH	1 DAY						

OPTION



FACTORY

