# KERN GAB30K0.2N

Checkweighing and portioning scale, also with EC type approval [M]





Measuring system	
Adjustment options:	External calibration
Eccentric loading at 1/3 [Max]:	
• • •	1 g
Linearity:	600 mg
Readability [d]:	200 mg
Recommended adjusting weight:	20 kg (F1); 10 kg (F1)
Repeatability:	200 mg
Resolution:	150000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-30 kg
Warm up time:	2 h
Weighing capacity [Max]:	30 kg
Weighing system:	Strain gauge
Weighing units:	g oz kg t lb
Display	
Display digit height (large):	2,400 cm
Counting	
Counting resolution:	150000
Mininum piece weight at piece counting (Laboratory:	200 mg
Mininum piece weight at piece counting (Normal):	2 g
Functions	
Counting function:	yes
Function to save totals:	yes
Percentage determination:	yes
Weighing with tolerance range:	yes

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	O°C
Minimum humidity:	0 %
Dowor oupply	
Power supply	
Charging time:	12 h
Input voltage:	220 V - 240 V AC 50 Hz
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	EURO UK CH
Operating time (Backlight off):	90 h
Operating time (Backlight on):	40 h
Rechargeable battery:	Rchrg. battery optional -
	intern
Services (optional)	
DAkkS Certificate:	963-128
	000 120
Category	
Brand:	KERN
Category:	Balances
Product Group:	Bench scale
Dockoging & chipping	
Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	450 x 375 x 210 mm
Gross weight:	4,300 kg
Net weight:	3 kg
Shipping method:	Parcel service
Construction	
Casing material:	Plastic
Dimensions housing (WxDxH):	315 x 350 x 100 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Overall dimensions mounted	315 x 350 x 125 mm
(WxDxH):	
Revolving screw feet:	yes
Weighing surface (WxD):	295 x 225 mm

# KERN GAB30K0.2N

Checkweighing and portioning scale, also with EC type approval [M]



### Piktogramme

#### STANDARD

### OPTION



FACTORY

